

SG105 / SG108

Gigabit forwarding Intelligent and easy to use

5 / 8 Port Gigabit Ethernet Switch

SG105/SG108 is a gigabit Ethernet switch, of high performance and easy maintenance. The switch is dedicated to a high speed forward demand like schools, small business offices, tiny enterprises and other small places. With an attractive MINI desktop design, and 5/8 ports, it is particularly suitable for small-size network. It also provides 5/8 10/100/1000Mbps auto-negotiation ports, and supports automatic MDI/MDIX. These gigabit ports can not only be used as ordinary ports, but can also cascade to other network devices through UPLINK port. In full duplex mode, SG105/SG108 can be used to replace the 10, 100 Mbps switch, to solve the bottleneck problem of the server terminal connection.



Gigabit speed

provide 5/8 10/100/1000Mbps adaptive port, all ports wire-speed forwarding, up to 1000 megabits per second.



Intelligent recognition

the ports can automatically identify the parallel line and intersecting line without pertinent setup.



Plug and play Compliance

it can be used directly when your line is connected, without special setup .

Specifications

		SG105	SG108
Hardware Features	Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab	
	Interface	5*10/100/1000M auto-negotiation RJ45 ports (Auto MDI/MDIX)	8*10/100/1000M auto-negotiation RJ45 ports (Auto MDI/MDIX)
	Transmission Media	Recommend Cat.5e UTP or better(<100 meters)	
	Forwarding Speed	10Mbps: 14880pps 100Mbps: 148800pps 1000Mbps: 1488000pps	
	Power Supply	Input: AC:100-240V; 50/60Hz Output: 5.0V 0.6A (External Power Adapter)	Input: AC:100-240V; 50/60Hz Output: 9.0V 0.6A (External Power Adapter)
	Product Dimensions (L*W*H)	93*66*23mm	142*90*24mm
	LEDs	1* Power, 5* Link/Act	1* Power, 8* Link/Act
	Switching Capacity	10Gbps	16Gbps
	MAC Address Table	4K	
	Power Consumption	Maximum : 1.7W (5V DC)	Maximum : 4W (9V DC)
Software Features	Transfer Method	Store and Forward	
	Access Control	CDMA/CD	
	MAC Address Learning	Automatic update	
Others	Temperature	Operating Temperature: 0℃~40℃ Storage Temperature: -40℃~70℃	
	Humidity	Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing	
	Certification	CE , FCC , RoHS	
	Related Products	L8139D 10/100M Network Adapter S16 16-Port 10/100Mbps Desktop Switch TEG1008D 8-Port Gigabit Desktop Switch	
	Compatible OS	Windows 8 32/64 bit , Windows 7 32/64 bit , Windows xp 32/64 bit , Linux , MAC OS	
	Package Contents	5-Port Gigabit Ethernet Switch Power Adapter (5V0.6A) Quick Installation Guide	8-Port Gigabit Ethernet Switch Power Adapter (9V0.6A) Quick Installation Guide

SHENZHEN TENDA TECHNOLOGY CO., LTD.

Tenda Technology Bldg. Int'l E-City, # 1001 Zhong Shan Yuan Rd. ,Nanshan District, Shenzhen 518055,China

Phone: (86 755) 2765 7180 Fax:(86 755) 2765 7178

Email: sales@tenda.com.cn support@tenda.com.cn

Http: www.tendacn.com



© 2013 SHENZHEN TENDA TECHNOLOGY CO.,Ltd, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.